



TIGOCEM WATERPROOF CEMENT PAINT is a Premium Cement Paint, specially designed for better paint brush ability, easy mixing and application, longer pot-life and extra coverage. It is the best protective cement paint coat against moisture and decay. Based on White Cement and special additives this is easy to apply and increases water repellence. It contains heat and UV resistant Oxide Pigments that are long lasting and eco-friendly.

SURFACE PREPARATION : The surface plaster or new surfaces must be cured completely for at least 28 days before paint application.

CLEANING : Clean the surface completely and remove accumulated fungus, algae or moss.

FILLING : For filling cracks up to 3 mm, holes and dents use **Tigonis Waterproof Wall Putty** and fine sand in the ratio 1:3 for exterior surfaces or substrates. Repair work is a MUST before application.

BEST USED ON

- Concrete surfaces • Wall & fiberboards • Asbestos cement sheets • Cement / Lime / Sand Renderings • Rough Cast & Pebbledash • Sand lime bricks • Concrete blocks • Decorative cement products • Concrete precast units

PERFORMANCE FEATURES

- High Strength • Breathable paint • Superior Brush ability • Economical protection • Durable, Waterproof Surface • Repels Rain on external surfaces • Greater coverage • Longer pot life • Anti –flaking properties

COVERAGE : 45-50Sq. Ft per Kg per Coat.*

*Conditions Apply.



TECHNICAL DATA

Appearance	Fine powder form
Colour	Available in many attractive shades
Finish	Beautiful matt finish
Curing	1st coat & 2nd coat should be cured properly
Drying Time	6-8 hours depending on climatic conditions
Mode of Application	Either to be brushed or sprayed
Re-coating period	18-24 hours depending on climatic condition.
Dry Film Thickness	50-60 microns
Coverage	45-50 sq.ft./ kg.

PRECAUTIONS : Sprinkle clean & fresh water onto the painted surface once or twice a day depending on weather condition. The process should be continued for at least two days following application of the final coat. This is essential for the proper curing of the paint. Do not use saline water for spray. Avoid paint application under strong, direct sun as this may create problem such as fast drying, brush marks & even patchy surface. If the surface is too adsorbent, then the 1st coat may have to be applied with more than usual thinning. Do not paint when it is raining.

HANDLING & STORAGE : Keep sacks airtight during and storage to avoid loss of material. Store in a cool dry place and also protect from extreme climatic conditions during storage, in transit and at site.

PACK SIZE : 25 Kg Bag (Available in Premium & Super Quality)

SHELF LIFE : 1 year (12 months) from the date of manufacturing.