

TIGONIS EXTERIOR PRIMER



**PREMIUM
QUALITY**



TIGONIS™

TIGONIS EXTERIOR WALL PRIMER is an acrylic based water-thinnable wall coating suitable for application on exteriors as an undercoat to exterior emulsions on exterior masonry surfaces. It acts as a sealer coat to prevent the excess absorption of decorative paints and enhances the overall coverage of the finish coats.

ADVANTAGES

- ▶ Does not chalk
- ▶ Can be applied on adequately cured fresh plaster
- ▶ Does not require curing with water
- ▶ Provides excellent adhesion to top coat emulsions
- ▶ Prevents peeling off/flaking of top coat emulsions



Bright and Brilliant...



TIGONIS EXTERIOR PRIMER

Bright and Brilliant...

THE BEST UNDERCOAT



PRECAUTIONS

Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application. Do not over-thin or over-extend the brush. Do not use stainers or any other colourants. Stir well and strain before use.



TECHNICAL SPECIFICATIONS

Colour	White
Drying time	Within 30 mins
Recoat Time	After 4-5 hours
Over Coating Interval	8 hours
Coverage	10 to 12 sq meters per litre per coat
Stability	To be used within 24 hours
Pack Sizes	1 Lt. 4 Lt. 10 Lt. & 20 Lt.
Areas of application	Exterior Plastered Surfaces & Concrete

SURFACE PREPARATION

Ensure surface is dry and free from old paint, dirt, grease, loose particles, algae & fungi. Rub the surface with 180 grade Emery/Sand paper and wipe clean. Dilute Primer with approximately 15-20% clean water to get application consistency. Stir the mixture well to avoid lumps. Now apply the first coat and allow it to dry for minimum 4-5 hours. Now apply the second coat and rub the surface with 320 grade Emery/Sand paper.



BENGAL BUILDING SOLUTIONS PVT. LTD.

57 G, K. N. Sen Road, Kolkata - 700042, Phone : 033 - 24430337/38

E: info@bbspl.co.in | W: www.bbspl.co.in

Works : Vill: Debipur, P. O. - Bhatheria, P. S. - Falta, District : 24 PGs (South) West Bengal, Pin : 743503