

**TECHNICAL DATA**

|                     |                                              |
|---------------------|----------------------------------------------|
| Appearance          | Fine powder form                             |
| Colour              | Available in many attractive shades          |
| Finish              | Beautiful matt finish                        |
| Curing              | 1st coat & 2nd coat should be cured properly |
| Drying Time         | 6-8 hours depending on climatic conditions   |
| Mode of Application | Either to be brushed or sprayed              |
| Re-coating period   | 18-24 hours depending on climatic condition. |
| Dry Film Thickness  | 50-60 microns                                |

**PRECAUTIONS** : Sprinkle clean & fresh water onto the painted surface once or twice a day depending on weather condition. The process should be continued for at least two days following application of the final coat. This is essential for the proper curing of the paint. Do not use saline water for spray. Avoid paint application under strong, direct sun as this may create problem such as fast drying, brush marks & even patchy surfaces. If the surface is too adsorbent, then the 1st coat may have to be applied with more than usual thinning. Do not paint when it is raining.

**HANDLING & STORAGE** : Keep sacks airtight during and storage to avoid loss of material. Store in a cool dry place and also protect from extreme climatic conditions during storage, in transit and at site.

**PACK SIZE** : 25-Kg Bag (Available in Premium & Super Quality)

**SHELF LIFE** : 1 year (12 months) from the date of manufacturing.



**TIGOCEM**

**STORAGE TIPS**

DO NOT EXPOSE TO ATMOSPHERE FOR LONG. STORE IN A COOL DRY PLACE.  
KEEP AWAY FROM REACH OF CHILDREN.

**CAUTION**

MAY CAUSE IRRITATION TO SKIN & EYES. AVOID INHALING DURING USAGE.



MANUFACTURED FOLLOWING BIS STANDARDS

Marketed By : Bengal Building Solutions Pvt. Ltd.

57 G, K. N. Sen Road, Kolkata - 700042

P: 033 - 24430337/38 | E: info@bbspl.co.in | W: www.bbspl.co.in

**A WIDE RANGE OF CONSTRUCTION PRODUCTS**

**TIGOCEM**

THE BEST WATER RESISTANT CEMENT PAINT

**WATERPROOF CEMENT PAINT**

HIGHER COVERAGE | LONGER POT LIFE  
SUPERIOR BRUSH ABILITY



**TIGOCEM WATERPROOF CEMENT PAINT** is a Premium Cement Paint, specially designed for better paint brush ability, easy mixing and application, longer pot-life and extra coverage. It is the best protective cement paint coat against moisture and decay. Based on White Cement and special additives this is easy to apply and increases water repellence. It contains heat and UV resistant Oxide Pigments that are long lasting and eco-friendly.

**SURFACE PREPARATION** : The surface plaster or new surfaces must be cured completely for at least 28 days before paint application.

**CLEANING** : Clean the surface completely and remove accumulated fungus, algae or moss.

**FILLING** : For filling cracks up to 3 mm, holes and dents use Tigonis Waterproof Wall Putty and fine sand in the ratio 1:3 for exterior surfaces or substrates. Repair work is a MUST before application.

**BEST USED ON**

• Concrete surfaces • Wall & fiberboards • Asbestos cement sheets • Cement / Lime / Sand Renderings • Rough Cast & Pebbledash • Sand lime bricks • Concrete blocks • Decorative cement products • Concrete precast units

**PERFORMANCE FEATURES**

• High Strength • Breathable paint • Superior Brush ability • Economical protection • Durable, Waterproof Surface • Repels Rain on external surfaces • Greater coverage • Longer pot life • Anti-falking properties

**MIXING** : To one volume of fresh water in a clean container add equal volume of Tigonis waterproof cement paint (1:1). Stir well. No further dilution is required and Tigonis is ready for application.

**PAINT APPLICATION - SURFACE PREPARATION & PRE-WETTING** : Scrub and clean the surface thoroughly. This is important for proper adhesion of the cement paint onto the surface. Pre-wet the surface with clean water & wait for 30 minutes.

**PREPARATION OF MIXED PAINT FOR APPLICATION** : Add one part of Tigonis with one part of clean water & mixed it continuously until a creamy consistency is obtained. It is important the same dilution is done each time in order to get uniform finish & shade. Also only sufficient of paint should be prepared at a time for consumption within 1 hour otherwise the paint might be set before application.

**APPLICATION OF PAINTS** : Application can be done with a coarse distemper brush, working well into the textured surface. For normal surface, two coats of paint will give satisfactory result.

**COVERAGE** : 45-50Sq. Ft per Kg per Coat.\*

\*Conditions Apply.

|                            |                              |                            |                          |
|----------------------------|------------------------------|----------------------------|--------------------------|
|                            |                              |                            |                          |
| WHITE (CODE : BB001)       | IVORY (CODE : BB002)         | SPL. BLUE (CODE : BB009)   | BRICK RED (CODE : BB010) |
|                            |                              |                            |                          |
| MID CREAM (CODE : BB003)   | LIGHT OLIVE (BB004)          | BRIGHT PINK (CODE : BB011) | PEACH (CODE : BB012)     |
|                            |                              |                            |                          |
| AQUAMARINE (CODE : BB005)  | SPECIAL GREEN (CODE : BB006) |                            |                          |
|                            |                              |                            |                          |
| APPLE GREEN (CODE : BB007) | SKY BLUE (CODE : BB008)      |                            |                          |

We also manufacture and customize other shades as per requirement.